

# ADESTOR Gloss 60

FACESTOCK

## Gloss 60

*Description* Gloss coated woodfree paper.

*Applications* Specially recommended for the labelling of fruits and vegetables such as tomatoes, oranges, watermelons, apples and for use in pharmaceutical industry, more specifically for test tubes and cylindrical products with a small diameter.

*Printing techniques* Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	60	57.6 - 62.4
Thickness	ISO 534	µm	52	48-56
Bekk smoothness	ISO 5627	s	≥ 600	
Brightness ISO	ISO 2470-2	%	90	87-93
Opacity	ISO 2471	%	76-83	
Paper gloss 20°	ISO 8254-1	%	85	± 5
Tensile strength MD/CD	ISO 1924	kN/m	≥ 3 / ≥ 1.7	

## Certificates

### Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

- Values are subject to change without notice. Last updated 10/20/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds ISO 9001 quality certification, ISO 14001 and EMAS environmental certifications and ISO 50001 energy management system certification. Adestor products are available with PEFC™ and FSC® chain of custody certificates upon request.