

ADESTOR Gloss 60

FACESTOCK

Gloss 60

Description Low substance gloss coated woodfree paper.

Color White

Finish Gloss

Applications For small diameter containers and the food sector.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|------------------|-------------|-------------|
| Substance | ISO 536 | g/m ² | 60 | 57.6 - 62.4 |
| Thickness | ISO 534 | µm | 52 | 48-56 |
| Bekk smoothness | ISO 5627 | s | ≥ 600 | |
| Brightness ISO | ISO 2470-2 | % | 90 | 87-93 |
| Opacity | ISO 2471 | % | 76-83 | |
| Paper gloss 20° | ISO 8254-1 | % | 85 | ± 5 |
| Tensile strength MD/CD | ISO 1924 | kN/m | ≥ 3 / ≥ 1.7 | |

Certificates

Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

- Values are subject to change without notice. Last updated 3/19/2018.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive is certified to the strictest environmental standards **ISO 9001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and OHSAS 18001**. Adestor products are available with **PEFC™ and FSC®** chain of custody certificates upon request.