High Gloss WS 80

Facestock

High Gloss WS 80

Description
Cast coated wet-strength woodfree paper with a high resistance to creasing, friction, breakage and tearing.

Applications
Luxury labels requiring a wet-strength face stock. Specially indicated for beverage labels as wines, spirits, champagnes.

Printing techniques
Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, conventional

offset UV, screen printing, stamping (hot and cold).

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	± 4%
Thickness	ISO 534	μm	76	± 4
Bekk smoothness	ISO 5627	S	1500	≥ 400
Brightness ISO	ISO 2470	%	89	± 2
Whiteness CIE	ISO 11475	%	106	± 5
Paper gloss	TAPPI T653 pm- 07	%	40	± 5
Opacity	ISO 2471	%	90	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	3,9 / 2,6	-0,6 / -0,3
Wet tensile strength MD/CD	ISO 3781	kN/m	0,9 / 0,8	≥ 0,6 / ≥ 0,4

Values are subject to change without notice. Last updated 1/1/2024.

* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.