## Fluor Yellow

Facestock

Fluor Yellow

Description Matt coated woodfree paper with a yellow fluorescent coating.

Color Yellow

Applications Eye-catching labels for pricing, display, promotions and warning signs.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), hot stamping, laser, conventional offset, offset UV, screen printing, thermal transfer.

| Property               | Norm         | Units | Value   | Tolerance    |
|------------------------|--------------|-------|---------|--------------|
| Substance              | ISO 536      | g/m²  | 80      | 76-84        |
| Thickness              | ISO 534      | μm    | 82      | 77-87        |
| Bekk smoothness        | ISO 5627     | s     | 250     | ≥ 200        |
| Tensile strength MD/CD | ISO 1924     | kN/m  | 5,5/2,6 | ≥ 4,5/ ≥ 2,2 |
| Flatness               | TAPPI UM 427 | mm    | ≤30     |              |

Values are subject to change without notice. Last updated 1/1/2024.

\* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.