## **PVC Gloss White**

Facestock

## **PVC Gloss White**

Description	Monomeric plasticised polyvinyl-chloride film with good dimensional stability.
Color	White
Finish	Gloss
Applications	Used in a variety of applications: POS promotional, eye-catching and warning labels. Suitable for indoor and also for outdoor short-term campaigns.
	Suitable for printing on UV flexo, conventional offset, letterpress (conventional and UV), hot stamping, Inkjet (solvent, mild solvent, UV and latex).

Property	Norm	Units	Value	Tolerance
Substance	ASTM D 1593	g/m²	110	104.4 - 115.4
Thickness	ASTM D 1593	μm	80	72-88
Gloss 60°	ASTM D 523	%	> 80	≥ 65
Surface tension	DIN 53364	dina/cm	≥ 36	
Dimensional stability 100°C 10min MD	ASTM D 1204	%	-5	5
Dimensional stability 100°C 10min CD	ASTM D 1204	%	-2	± 2

- Values are subject to change without notice. Last updated 1/1/2024.

\* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.