

Vellum Duplex (A251/GA62)

Facestock

Vellum Duplex (A251/GA62)

- Description* Complex formed by Offset facestock (calendered uncoated woodfree paper), A251 permanent adhesive and yellow glassine liner 62 gsm.
- Applications* Extensively used in logistics for shipping and courier applications.
- Printing techniques* Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, hot stamping, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	155	70-76
Thickness	ISO 534	µm	141	± 2
Bekk smoothness	ISO 5627	s	≥250	
Brightness ISO	ISO 2470-2	%	101.5	± 2
Whiteness CIE	ISO 11475	%	158.2	± 5
Opacity	ISO 2471	%	89	-2
Wet tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

- * Values are subject to change without notice. Last updated 1/1/2024.
- * The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.