

ADESTOR Matt 170

FACESTOCK

Matt 170

Description Matt coated woodfree paper.

Applications For promotional inserts.

Printing techniques Suitable for printing on laser, flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	170	± 4%
Thickness	ISO 534	µm	152	± 4%
Bekk smoothness	ISO 5627	s	160	± 4%
Brightness ISO	ISO 2470-2	%	96	± 2
Whiteness CIE	ISO 11475	%	120	± 3
Opacity	ISO 2471	%	97,0	-2.0
Paper gloss 20°	ISO 8254-1	%		
Tensile strength MD/CD	ISO 1924-2	kN/m		

Certificates

Product approvals and usage certificates

EN 1230 Sensorial analysis

Toy safety European directive 2009/48/CE

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

- Values are subject to change without notice. Last updated 10/20/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive is certified to the strictest environmental standards **ISO 9001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and OHSAS 18001**. Adestor products are available with **PEFC™ and FSC®** chain of custody certificates upon request.