

Vellum Duplex(SP123/GA62)

Facestock

Vellum Duplex(SP123/GA62)

Description Complex formed by Vellum facestock (calendere uncoatedwoodfree paper), SP123 superpermanent adhesive and yellow glassine liner 62 gsm

Applications Extensively used in logistics for shipping and courier applications.

Printing techniques Suitable for printing on flexo (all types), hot stamping, laser, conventional offset, offset UV, screen printing, letterpress (conventional and UV), thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	159	70-76
Thickness	ISO 534	µm	144	± 2
Bekk smoothness	ISO 5627	s	≥ 250	
Brightness ISO	ISO 2470-2	%	101.5	± 2
Opacity	ISO 2471	%	89	-2
Wet tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

- Values are subject to change without notice. Last updated 1/1/2024.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.