

ADESTOR VR152

ADHESIVE

VR152

Description Acrylic permanent adhesive for recyclable bottles with a completely satisfactory behaviour of the label in caustic soda solution and ice water. Always used with wet strength face stock.

Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 11,5 | ≥ 9,1 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 28 | ≥ 18 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 10,1 | ≥ 7,8 |
| Minimum labelling temperature | | °C | -20 | |
| Minimum service temperature | | °C | -40 | |
| Maximum service temperature. | | °C | +60 | |

Certificates

Product approvals and usage certificates

Direct contact with foodstuffs (ISEGA) - Adhesives

- Values are subject to change without notice. Last updated 10/21/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds **ISO 9001** quality certification, **ISO 14001** and **EMAS** environmental certifications and **ISO 50001** energy management system certification. Adestor products are available with **PEFC™** and **FSC®** chain of custody certificates upon request.