

ADESTOR SP123

ADHESIVE

SP123

Description Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	17,2	≥ 13,5
Shear (1kg, in ² /glass)	FTM 8	min	100	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	11	≥ 9,8
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Certificates

Product approvals and usage certificates

EN 71-3 Toy safety

EN 71-9 Toy safety

Packaging and packaging waste Directive 94/62/CE

Direct contact with foodstuffs (ISEGA) - Adhesives

- Values are subject to change without notice. Last updated 10/21/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill holds **ISO 9001** quality certification, **ISO 14001** and **EMAS** environmental certifications and **ISO 50001** energy management system certification. Adestor products are available with **PEFC™** and **FSC®** chain of custody certificates upon request.