# Laid Cream 90 WS / VR152 / GW80

Facestock

## Laid Cream 90 WS

Description	Uncoated wet-strength woodfree laid paper with a textured finish.
Color	Cream
	Specially designed for prestige labels for wine, spirits and gourmet products.
Printing techniques	Suitable for printing on conventional offset, offset UV, screen printing, hot stamping, flexo water- based, flexo solvent-base, UV flexo.

SubstanceISO 536g/m²90ThicknessISO 524um122	e Tolerance	Value	Units	Norm	Property
Thiskness ISO 524 ym 122	± 4%	90	g/m²	ISO 536	Substance
Thickness 150 534 µm 125	± 5%	123	μm	ISO 534	Thickness
Tensile strength MD/CDISO 1924kN/m $\geq$ 7/ $\geq$ 4	4	$\geq 7/ \geq 4$	kN/m	ISO 1924	Tensile strength MD/CD

#### Adhesive

## VR152

Description Acrylic permanent adhesive for recyclable bottles with a completely satisfactory behaviour of the label in caustic soda solution and ice water. Always used with wet strength face stock. Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180º 20'/stainless steel)	FTM 1	N/25mm	11,5	≥ 9,1
Tack (Quick Stick stainless steel)	FTM 9	Ν	10,1	≥ 7,8
Shear (1kg, in²/glass)	FTM 8	min	28	≥ 18
Minimum labelling temperature		°C	-20	
Minimum service temperature		°C	-40	
Maximum service temperature.		°C	+60	

## Liner

## **Glassine White 80**

Super-calendared translucent glassine paper especially designed for automatic labelling Description applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Applications For those applications where extra thickness of the backing paper is required such as wine labelling and filmic applications.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	77-83
Thickness	ISO 534	μm	68	64-72

Values are subject to change without notice. Last updated 1/1/2024.

\* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO



45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

Lecta Main Operational Offices Self-Adhesive Division Llull, 331 - 08019 Barcelona - Spain www.adestor.com