

# Matt 80

Facestock

## Matt 80

*Description* Matt coated woodfree paper.

*Applications* Standard label applications with matt finish.

*Printing techniques* Suitable for printing on laser, flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping.

| Property        | Norm       | Units            | Value | Tolerance |
|-----------------|------------|------------------|-------|-----------|
| Substance       | ISO 536    | g/m <sup>2</sup> | 80    | ± 4%      |
| Thickness       | ISO 534    | µm               | 74    | ± 4%      |
| Bekk smoothness | ISO 5627   | s                | ≤100  |           |
| Brightness ISO  | ISO 2470-2 | %                | 96    | ± 2       |
| Whiteness CIE   | ISO 11475  | %                | 119   | ± 3       |
| Opacity         | ISO 2471   | %                | 90    | -2        |

## Certificates

### Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Toy safety European directive 2009/48/CE

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 3/20/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification.  
Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.