

# ADESTOR Gloss 60

FACESTOCK

## Gloss 60

*Description* Low substance gloss coated woodfree paper.

*Color* White

*Finish* Gloss

*Applications* For small diameter containers and the food sector.

*Printing techniques* Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

| Property               | Norm       | Units            | Value       | Tolerance   |
|------------------------|------------|------------------|-------------|-------------|
| Substance              | ISO 536    | g/m <sup>2</sup> | 60          | 57.6 - 62.4 |
| Thickness              | ISO 534    | µm               | 52          | 48-56       |
| Bekk smoothness        | ISO 5627   | s                | ≥ 600       |             |
| Brightness ISO         | ISO 2470-2 | %                | 90          | 87-93       |
| Opacity                | ISO 2471   | %                | 76-83       |             |
| Paper gloss 20°        | ISO 8254-1 | %                | 85          | ± 5         |
| Tensile strength MD/CD | ISO 1924   | kN/m             | ≥ 3 / ≥ 1.7 |             |

## Certificates

### Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 3/19/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive is certified to the strictest environmental standards **ISO 9001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and OHSAS 18001**. Adestor products are available with **PEFC™ and FSC®** chain of custody certificates upon request.