

Gloss 60

Facestock

Gloss 60

Description Low substance gloss coated woodfree paper.

Applications For small diameter containers and the food sector.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	60	57.6 - 62.4
Thickness	ISO 534	µm	52	48-56
Bekk smoothness	ISO 5627	s	≥ 600	
Brightness ISO	ISO 2470-2	%	90	87-93
Opacity	ISO 2471	%	76-83	
Paper gloss 20°	ISO 8254-1	%	85	± 5
Tensile strength MD/CD	ISO 1924	kN/m	≥ 3 / ≥ 1.7	

Certificates

Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 10/10/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.