

# ADESTOR Gloss 80

FACESTOCK

## Gloss 80

*Description* Gloss coated woodfree paper.

*Color* White

*Finish* Gloss

*Applications* High resolution standard gloss label for multicolour printing. Extensively used in food and beverage industry, logistics, stationery and cosmetics products.

*Printing techniques* Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	80	± 4%
Thickness	ISO 534	µm	69	± 4%
Bekk smoothness	ISO 5627	s	≥ 850	
Brightness ISO	ISO 2470-2	%	93	± 2
Whiteness CIE	ISO 11475	%	117	±3
Opacity	ISO 2471	%	88,5	-2
Paper gloss 20°	ISO 8254-1	%	66	± 5
Tensile strength MD	ISO 1924-2	kN/m	4,9	-0,5

## Certificates

### Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 3/19/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive is certified to the strictest environmental standards **ISO 9001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and OHSAS 18001**. Adestor products are available with **PEFC™ and FSC®** chain of custody certificates upon request.