

Cardboard

Facestock

Cardboard

Description Gloss coated cardboard with high brightness and gloss.

Applications Suitable for those applications where high stiffness and/or thickness are required. Advertising, children's stickers and games.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	250	240-260
Thickness	ISO 534	µm	280	263-297
Brightness ISO	ISO 2470	%	87,55	85,8 - 89,3
Flatness	TAPPI UM 427	%	≥ 10	
Taber rigidity MD/CD	ISO 2493	mN.m	> 4,93 / > 2,29	

Certificates

Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 71-3 Toy safety

- Values are subject to change without notice. Last updated 10/21/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.