

# Acetate

Facestock

## Acetate

*Description* Clear glossy tear-resistant cellulose acetate film.

*Color* Clear

*Finish* Gloss

*Applications* Clear labels predominantly used for cosmetics and quality indoor advertising. Not suitable for outdoor use due to extreme sensitivity to harsh weather conditions and/or solvents.

*Printing techniques* Suitable for printing on UV flexo, offset UV, conventional offset, letterpress (conventional and UV), hot stamping, screen printing.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	65	62.2-68.8
Thickness	ISO 534	µm	50	46-54
Dimensional stability 100°C 10min MD	ASTM D 1204	%	-1	± 1
Dimensional stability 100°C 10min CD	ASTM D 1204	%	-1	± 1

## Certificates

### Product approvals and usage certificates

Food contact according to Directive 2002/72/EC

EN 71-3 Toy safety

- Values are subject to change without notice. Last updated 10/21/2016.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.