

# PVC Gloss Clear

Facestock

## PVC Gloss Clear

*Description* Monomeric plasticised polyvinyl-chloride film with good dimensional stability.

*Color* Clear

*Finish* Gloss

*Applications* Used in a variety of applications: POS promotional, eye-catching and warning labels. Suitable for indoor and also for outdoor short-term campaigns.

*Printing techniques* Suitable for printing on UV flexo, conventional offset, letterpress (conventional and UV), hot stamping, Inkjet (solvent, mild solvent, UV and latex).

| Property                             | Norm        | Units            | Value | Tolerance |
|--------------------------------------|-------------|------------------|-------|-----------|
| Substance                            | ASTM D 1593 | g/m <sup>2</sup> | 105   | 99 - 110  |
| Thickness                            | ASTM D 1593 | µm               | 80    | 72-88     |
| Gloss 60°                            | ASTM D 523  | %                | ≥ 90  |           |
| Dimensional stability 100°C 10min MD | ASTM D 1204 | %                | -5    | 5         |
| Dimensional stability 100°C 10min CD | ASTM D 1204 | %                | -2    | ± 2       |
| Surface tension                      | DIN 53364   | dina/cm          | ≥ 36  | ≥ 36      |

## Certificates

### Product approvals and usage certificates

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 2/26/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

*Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.*