

PVC White

Facestock

PVC White

Description Monomeric plasticised polyvinyl-chloride film with good dimensional stability.

Color White

Finish Gloss

Applications Used in a variety of applications: POS promotional, eye-catching and warning labels. Suitable for indoor and also for outdoor short-term campaigns.

Printing techniques Suitable for printing on UV flexo, conventional offset, letterpress (conventional and UV), hot stamping, Inkjet (solvent, mild solvent, UV and latex).

Property	Norm	Units	Value	Tolerance
Substance	ASTM D 1593	g/m ²	110	104.4 - 115.4
Thickness	ASTM D 1593	µm	80	72-88
Gloss 60°	ASTM D 523	%	> 80	≥ 65
Dimensional stability 100°C 10min MD	ASTM D 1204	%	-5	5
Dimensional stability 100°C 10min CD	ASTM D 1204	%	-2	± 2
Surface tension	DIN 53364	dina/cm	≥ 36	

Certificates

Product approvals and usage certificates

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 10/10/2017.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001** and **EMAS** and has successfully completed audits for **ISO 50001**, **ISO 9001** and **ISO 45001** certification. Adestor paper products are available with **PEFC™** and **FSC®** chain of custody certificates upon request.