

# Thermal Top + Piggyback (SP123/YG62) BPA Free

Facestock

## Thermal Top + Piggyback (SP123/YG62) BPA Free

*Description* Complex formed by Thermal Top+ facestock (top coated thermal paper with back barrier without Bisphenol A), SP123 super-permanent adhesive and yellow glassine liner 62 gsm.

*Applications* Extensively used in logistics for shipping and courier applications.

*Printing techniques* Suitable for printing on offset UV, UV flexo, flexo solvent-base depending on the ink.

| Property                   | Norm     | Units | Value           | Tolerance |
|----------------------------|----------|-------|-----------------|-----------|
| Substance                  | ISO 536  |       | 72              | 67-77     |
| Thickness                  | ISO 534  |       | 73              | 67-79     |
| Bekk smoothness            | ISO 5627 |       | ≥ 500           |           |
| Brightness ISO             | ISO 2470 |       | ≥ 80            |           |
| Wet tensile strength MD/CD | ISO 1924 |       | ≥ 3,59 / ≥ 1,63 |           |

## Facestock sensitivity curves

Dynamic Sensitivity

Static Sensitivity

## Additional information

### Durability

Up to 2 years if kept wrapped at a temperature of below 25°C and relative humidity of 50%.

Values are subject to change without notice. Last updated 1/17/2019.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.