

Tag Gloss PET 30µm

Facestock

Tag Gloss PET 30µm

Description Gloss coated woodfree paper laminated on PET 30µm.

Finish Gloss

Applications Specially recommended for the labelling of boxes for fruit and vegetables.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

| Property | Norm | Units | Value | Tolerance |
|---------------------|------------|------------------|-------|-----------|
| Substance | ISO 536 | g/m ² | 138 | ±5% |
| Thickness | ISO 534 | µm | 111 | ±5% |
| Bekk smoothness | ISO 5627 | s | ≥850 | |
| Brightness ISO | ISO 2470-2 | % | 93 | ±2 |
| Whiteness CIE | ISO 11475 | % | 117 | ±3 |
| Opacity | ISO 2471 | % | 88.5 | -2 |
| Paper gloss 20° | ISO 8254-1 | % | 66 | ±5 |
| Tensile strength MD | ISO 1924-2 | kN/m | 4.9 | -0.5 |

Values are subject to change without notice. Last updated 3/11/2016.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001** and **EMAS** and has successfully completed audits for **ISO 50001**, **ISO 9001** and **ISO 45001** certification. Adestor paper products are available with **PEFC™** and **FSC®** chain of custody certificates upon request.