

Vellum Duplex

Facestock

Vellum Duplex

Description Complex formed by Offset facestock (calendered uncoated woodfree paper), SP123 super-permanent adhesive and yellow glassine liner 62 gsm.

Applications Extensively used in logistics for shipping and courier applications.

Printing techniques Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, hot stamping, laser.

| Property | Norm | Units | Value | Tolerance |
|----------------------------|------|-------|---------|-----------|
| Substance | | | 135 | 70-76 |
| Thickness | | | 137 | ± 2 |
| Bekk smoothness | | | ≥250 | |
| Brightness ISO | | | 101.5 | ± 2 |
| Whiteness CIE | | | 158.2 | ± 5 |
| Opacity | | | 89 | -2 |
| Wet tensile strength MD/CD | | | 5.0/3.0 | -1 |

Values are subject to change without notice. Last updated 7/12/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.