

CG349

Adhesive

CG349

Description Permanent adhesive with high adhesion on frozen surfaces. For labelling frozen and cold surfaces at very low temperature. Not recommended for frosted surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	13,7	≥ 10,3
Shear (1kg, in ² /glass)	FTM 8	min	35	≥ 20
Tack (Quick Stick stainless steel)	FTM 9	N	10,8	≥ 7,8
Minimum labelling temperature		°C	-35	
Minimum service temperature		°C	-40	
Maximum service temperature.		°C	+60	

Additional information

Should not be exposed to high temperatures and direct UV light.

Certificates

Product approvals and usage certificates

German Recommendation BfR XIV (ISEGA) - Adhesives

EN 71-3 Toy safety

Packaging and packaging waste Directive 94/62/CE

Values are subject to change without notice. Last updated 11/25/2019.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.