

# RA678

Adhesive

## RA678

*Description* Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces

*Shelf life* From the date of manufacture 1 year in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel stainless steel 1 week)	FTM 1	N/25mm	1,7	1 - 2,9
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	120	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	1,2	0,7 - 1,7
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

## Certificates

### Product approvals and usage certificates

EN 71-3 Toy safety

Packaging and packaging waste Directive 94/62/CE

- Values are subject to change without notice. Last updated 1/24/2018.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.