

# Vintack Ws White / A251 / YG62

Facestock

## Vintack WS White

*Description* Natural uncoated wet-strength woodfree paper with a textured finish.

*Color* White

*Applications* Ideal for prestige food labelling with a classic touch such as handmade products, delicatessen ranges and wines.

*Printing techniques* Suitable for printing on conventional offset, offset UV, screen printing, hot stamping, flexo solvent-base, UV flexo, flexo water-based.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	90	86 - 94
Thickness	ISO 534	µm	124	118 - 130
Tensile strength MD/CD	ISO 1924	kN/m	≥ 3,5 / ≥ 1,6	
Rugosidad	ISO 8791-2	ml/min	230	130 - 330

Adhesive

## A251

*Description* General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

*Shelf life* From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	15,4	≥ 12,3
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	100	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

## Glassine Ambar 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	62	59-65
Thickness	ISO 534	µ	52	50-58

## Certificates

### Product approvals and usage certificates

Facestock

#### **Vintack WS White**

Electric and electronic equipment (RoHS)

Adhesive

#### **A251**

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

EN 71-9 Toy safety

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

#### **Glassine Ambar 62**

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 3/20/2018.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

*Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.*