

Fluo Red / A251 / YG62

Facestock

Fluo Red

Description Matt coated woodfree paper with a red fluorescent coating.

Color Red

Applications Eye-catching labels for pricing, display, promotions and warning signs.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), thermal transfer, screen printing, laser, hot stamping.

| Property | Norm | Units | Value | Tolerance |
|------------------------|--------------|------------------|---------|--------------|
| Substance | ISO 536 | g/m ² | 80 | 76-84 |
| Thickness | ISO 534 | µm | 82 | 77-87 |
| Bekk smoothness | ISO 5627 | s | 250 | ≥ 200 |
| Tensile strength MD/CD | ISO 1924 | kN/m | 5.5/2.6 | ≥ 4.5/ ≥ 2.2 |
| Flatness | TAPPI UM 427 | mm | ≤30 | |

Adhesive

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 15,4 | ≥ 12,3 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 100 | ≥ 60 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 10,3 | ≥ 7,8 |
| Minimum labelling temperature | | °C | +5 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +80 | |

Liner

Glassine Ambar 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

| Property | Norm | Units | Value | Tolerance |
|-----------|---------|------------------|-------|-----------|
| Substance | ISO 536 | g/m ² | 62 | 59-65 |
| Thickness | ISO 534 | µ | 52 | 50-58 |

Certificates

Product approvals and usage certificates

Facestock

Fluo Red

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Adhesive

A251

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

EN 71-9 Toy safety

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

Glassine Ambar 62

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 4/7/2016.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.*