

Embossed Toile WS / BC500 / WG80

Facestock

Embossed Toile WS

Description One side embossed wet-strength coated paper with a toile finishing.

Color White

Finish Matt

Applications Presige labels for wine and delicatessen products.

Printing techniques Suitable for printing on UV flexo, offset UV.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	90	85,5 - 94,5
Thickness	ISO 534	μ	125	116 - 134
Whiteness CIE	ISO 11476	°CIE	152	
Opacity	ISO 2471	%	93	min. 90

Adhesive

BC500

Description Acrylic permanent adhesive for non-recyclable bottles. The printed label resists a minimum of 2 hours with the bottle being submerged ice water (Ice Test).

Shelf life From the date of manufacture, 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	17	≥ 15
Shear (1kg, in ² /glass)	FTM 8	min	400	≥ 180
Tack (Quick Stick stainless steel)	FTM 9	N	13	≥ 9
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

WG80

Description Super-calendared translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Applications For those applications where extra thickness of the backing paper is required such as wine labelling and filmic applications.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	77-83
Thickness	ISO 534	μm	68	64-72

Certificates

Product approvals and usage certificates

Facestock

Embossed Toile WS

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Adhesive

BC500

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

WG80

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 1/3/2020.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.*