

# Gloss 80 / HM100 / YG62

## Facestock

### Gloss 80

*Description* Gloss coated woodfree paper.

*Applications* High resolution standard gloss label for multicolour printing. Extensively used in food and beverage industry, logistics, stationery and cosmetics products.

*Printing techniques* Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	80	± 4%
Thickness	ISO 534	µm	67	± 4%
Bekk smoothness	ISO 5627	s	≥ 850	
Brightness ISO	ISO 2470-2	%	93	± 2
Whiteness CIE	ISO 11475	%	117	±3
Opacity	ISO 2471	%	88,5	-2
Paper gloss 20°	ISO 8254-1	%	66	± 5
Tensile strength MD	ISO 1924-2	kN/m	4,9	-0,5

## Adhesive

### HM100

*Description* General use hot-melt permanent adhesive, designed to achieve good performance when used at chilled conditions. For difficult surfaces, slightly wet and semi-frozen.

*Shelf life* From the date of manufacture 1 year in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	18,4	≥ 14,7
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	750	≥500
Tack (Quick Stick stainless steel)	FTM 9	N	13,5	≥11
Minimum labelling temperature		°C	0	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+60	

## Liner

### Glassine Ambar 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	62	59-65
Thickness	ISO 534	µ	52	50-58

## Certificates

### Product approvals and usage certificates

Facestock

#### **Gloss 80**

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Adhesive

#### **HM100**

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

#### **Glassine Ambar 62**

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 5/22/2020.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC™ and FSC®** chain of custody certificates upon request.*