Fluo Yellow / A251 / WG62

Facestock

Fluor Yellow

Description Matt coated woodfree paper with a yellow fluorescent coating.

Color Yellow

Applications Eye-catching labels for pricing, display, promotions and warning signs.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), hot stamping, laser, conventional offset, offset UV, screen printing, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	76-84
Thickness	ISO 534	μm	82	77-87
Bekk smoothness	ISO 5627	s	250	≥ 200
Tensile strength MD/CD	ISO 1924	kN/m	5,5/2,6	≥ 4,5/ ≥ 2,2
Flatness	TAPPI UM 427	mm	≤30	

Adhesive

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces. Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	15,4	≥ 12,3
Shear (1kg, in²/glass)	FTM 8	min	100	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Glassine White 62

Super-calendered translucent glassine paper especially designed for automatic labelling Description applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	62	59-65
Thickness	ISO 534	μm	52	49-55

Certificates

Product approvals and usage certificates

Facestock

Fluor Yellow

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Adhesive

A251

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

EN 71-9 Toy safety

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

Glassine White 62

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 4/6/2016.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC[™] and FSC® chain of custody certificates upon request.