

Foil Gold / SP123 / YG62

Facestock

Foil Gold

Description Aluminium foil laminated on satin 50 gsm paper. Available in gloss and matt finish.

Color Gold

Finish Gloss, Matt

Applications Decorative labels. High quality labels for cosmetics, spirits and the food industry in general.

Printing techniques Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent-base, hot stamping, screen printing, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	G/m ²	72	67,7 - 76,3
Thickness	ISO 534	µm	65	58,5 - 71,5

Adhesive

SP123

Description Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	17,2	≥ 13,5
Shear (1kg, in ² /glass)	FTM 8	min	100	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	11	≥ 9,8
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Glassine Ambar 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	62	59-65
Thickness	ISO 534	µ	52	50-58

Certificates

Product approvals and usage certificates

Facestock

Foil Gold

Packaging and packaging waste Directive 94/62/CE

Adhesive

SP123

EN 71-3 Toy safety

EN 71-9 Toy safety

Packaging and packaging waste Directive 94/62/CE

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

Glassine Ambar 62

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 2/3/2016.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.