Vintack White 95 WS / VR152 / GW80

Facestock

Vintack White 95 WS

Description Natural uncoated wet-strength woodfree paper with a textured finish.

Color White

Ideal for prestige food labelling with a classic touch such as handmade products, delicatessen *Applications* ranges and wines.

We recommend winding the labels reels with the face side out.

Printing techniques Suitable for printing on conventional offset, offset UV, screen printing, hot stamping, flexo solventbase, UV flexo, flexo water-based.

Norm	Units	Value	Tolerance
ISO 536	g/m²	95	± 4%
ISO 534	μm	129	± 5%
ISO 1924	kN/m	≥ 7,5 / ≥ 4,4	
	ISO 536 ISO 534	ISO 536 g/m² ISO 534 μm	ISO 536 g/m ² 95 ISO 534 μm 129

Adhesive

VR152

Description Acrylic permanent adhesive for recyclable bottles with a completely satisfactory behaviour of the label in caustic soda solution and ice water. Always used with wet strength face stock.

Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	11,5	≥ 9,1
Tack (Quick Stick stainless steel)	FTM 9	Ν	10,1	≥ 7,8
Shear (1kg, in²/glass)	FTM 8	min	28	≥ 18
Minimum labelling temperature		°C	-20	
Minimum service temperature		°C	-40	
Maximum service temperature.		°C	+60	

Liner

Glassine White 80

Super-calendared translucent glassine paper especially designed for automatic labelling *Description* applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Applications For those applications where extra thickness of the backing paper is required such as wine labelling and filmic applications.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	77-83
Thickness	ISO 534	μm	68	64-72

Values are subject to change without notice. Last updated 01/01/2025.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.