Matt Inkjet FSC® Certified / SP123 / WG62

Facestock

Matt Inkjet FSC® Certified

Description Matt coated woodfree paper for Inkjet printing. This product is sold as FSC® Mix Credit - FSC® C011032.

Color White

Finish Matt

Applications For all type of labels with excellent resolution. Used in the food and beverage industry, cosmetic products, retail or logistics.

Printing techniques Suitable for printing on inkjets.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	90	± 4
Thickness	ISO 534	μm	130	± 5
Whiteness CIE	ISO 11475	%	153	± 3
Opacity	ISO 2471	%	94	± 1

Adhesive

SP123

Description Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180º 20'/stainless steel)	FTM 1	N/25mm	17,2	≥ 13,5
Tack (Quick Stick stainless steel)	FTM 9	N	11	≥ 9,8
Shear (1kg, in²/glass)	FTM 8	min	100	≥ 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Glassine White 62

Super-calendered translucent glassine paper especially designed for automatic labelling Description applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	62	59 - 65
Thickness	ISO 534	μm	52	51 - 59

Values are subject to change without notice. Last updated 01/01/2025

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

^{*} The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.