

# Matt Inkjet FSC® Certified / SP123 / WG62

Facestock

## Matt Inkjet FSC® Certified

**Description** Matt coated woodfree paper for Inkjet printing. This product is sold as FSC® Mix Credit - FSC® C011032.

**Color** White

**Finish** Matt

**Applications** For all type of labels with excellent resolution. Used in the food and beverage industry, cosmetic products, retail or logistics.

**Printing techniques** Suitable for printing on inkjets.

| Property      | Norm      | Units            | Value | Tolerance |
|---------------|-----------|------------------|-------|-----------|
| Substance     | ISO 536   | g/m <sup>2</sup> | 83    | ± 4       |
| Thickness     | ISO 534   | µm               | 110   | ± 5       |
| Whiteness CIE | ISO 11475 | %                | 153   | ± 3       |
| Opacity       | ISO 2471  | %                | 94    | ± 1       |

Adhesive

## SP123

**Description** Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

**Shelf life** From the date of manufacture 2 years in 20°C and RH 50%

| Property                                 | Norm  | Units  | Value | Tolerance |
|------------------------------------------|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 17,2  | ≥ 13,5    |
| Tack (Quick Stick stainless steel)       | FTM 9 | N      | 11    | ≥ 9,8     |
| Shear (1kg, in <sup>2</sup> /glass)      | FTM 8 | min    | 100   | ≥ 60      |
| Minimum labelling temperature            |       | °C     | +5    |           |
| Minimum service temperature              |       | °C     | -20   |           |
| Maximum service temperature.             |       | °C     | +80   |           |

Liner

## Glassine White 62

**Description** Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

**Color** White

| Property  | Norm    | Units            | Value | Tolerance |
|-----------|---------|------------------|-------|-----------|
| Substance | ISO 536 | g/m <sup>2</sup> | 62    | 59 - 65   |
| Thickness | ISO 534 | µm               | 52    | 51 - 59   |

\* Values are subject to change without notice. Last updated 01/01/2024.

\* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

# TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.*