

Supertack

Adhesive

Supertack

Description Specially strong and aggressive acrylic permanent adhesive with excellent tack and final adhesion. For difficult surfaces such as wood boxes, slightly wet surfaces, rough plastics and LDPE.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 14 | ≥ 11,5 |
| Adhesion (Peel 180° 24h/kraft) | FTM 1 | N/25mm | 7,6 | ≥ 6,6 |
| Adhesion (Peel 180° 24h/LDPE) | FTM 1 | N/25mm | 250 | ≥ 5,4 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 12,3 | ≥ 9,8 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 15 | ≥ 10 |
| Minimum labelling temperature | | °C | -7 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +60 | |

- Values are subject to change without notice. Last updated 1/1/2025.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.