

Foil Silver / CE432 / BG62

Facestock

Foil Bright Silver

Description Aluminium foil laminated on satin 50 gsm paper. Available in gloss finish.

Color Silver

Finish Gloss

Applications Decorative labels. High quality labels for cosmetics, spirits and the food industry in general.

Printing techniques Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), flexo solvent-base, UV flexo, screen printing, hot stamping, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	72	67.7 - 76.3
Thickness	ISO 534	µm	65	58.5 - 71.5

Adhesive

CE432

Description A low tack acrylic semipermanent adhesive that permits repositioning upon application.

Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	16,7	≥ 12,3
Tack (Quick Stick stainless steel)	FTM 9	N	8,3	≥ 7,4
Shear (1kg, in ² /glass)	FTM 8	min	55	≥ 30
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Glassine Blue 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Blue

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	62	59 - 65
Thickness	ISO 534	µm	52	51 - 59

• Values are subject to change without notice. Last updated 01/01/2024.

• The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.