

# Foil Gold / BC500 / GA62

Facestock

## Foil Bright Gold

*Description* Aluminium foil laminated on satin 50 gsm paper. Available in gloss and matt finish.

*Color* Gold

*Finish* Gloss, Matt

*Applications* Decorative labels. High quality labels for cosmetics, spirits and the food industry in general.

*Printing techniques* Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent-base, hot stamping, screen printing, thermal transfer.

| Property  | Norm    | Units            | Value | Tolerance   |
|-----------|---------|------------------|-------|-------------|
| Substance | ISO 536 | G/m <sup>2</sup> | 72    | 67,7 - 76,3 |
| Thickness | ISO 534 | µm               | 65    | 58,5 - 71,5 |

Adhesive

## BC500

*Description* Acrylic permanent adhesive for non-recyclable bottles. The printed label resists a minimum of 2 hours with the bottle being submerged ice water (Ice Test).

*Shelf life* From the date of manufacture, 2 years in 20°C and RH 50%

| Property                                 | Norm  | Units  | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 17    | ≥ 15      |
| Tack (Quick Stick stainless steel)       | FTM 9 | N      | 13    | ≥ 9       |
| Shear (1kg, in <sup>2</sup> /glass)      | FTM 8 | min    | 400   | ≥ 180     |
| Minimum labelling temperature            |       | °C     | +5    |           |
| Minimum service temperature              |       | °C     | -20   |           |
| Maximum service temperature.             |       | °C     | +80   |           |

Liner

## Glassine Ambar 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* Yellow

| Property  | Norm    | Units            | Value | Tolerance |
|-----------|---------|------------------|-------|-----------|
| Substance | ISO 536 | g/m <sup>2</sup> | 56    | 55-57     |
| Thickness | ISO 534 | µ                | 48    | 46 - 49   |

- Values are subject to change without notice. Last updated 01/01/2024.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.