

# Vintack Cream 90 WS / VR152 / GW80

Facestock

## Vintack Cream 90 WS

*Description* Natural uncoated wet-strength woodfree paper with a textured finish.

*Color* Cream

*Applications* Ideal for prestige food labelling with a classic touch such as handmade products, delicatessen ranges and wines.

*Printing techniques* Suitable for printing on flexo solvent-base, UV flexo, flexo water-based, hot stamping, screen printing, conventional offset, offset UV.

| Property               | Norm    | Units            | Value         | Tolerance |
|------------------------|---------|------------------|---------------|-----------|
| Substance              | ISO 536 | g/m <sup>2</sup> | 90            | ± 4%      |
| Thickness              | ISO 534 | µm               | 123           | ± 5%      |
| Tensile strength MD/CD | kN/m    | kN/m             | ≥ 6,2 / ≥ 3,6 |           |

Adhesive

## VR152

*Description* Acrylic permanent adhesive for recyclable bottles with a completely satisfactory behaviour of the label in caustic soda solution and ice water. Always used with wet strength face stock.

*Shelf life* From the date of manufacture 2 years in +20°C and RH 50%.

| Property                                 | Norm  | Units  | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 11,5  | ≥ 9,1     |
| Tack (Quick Stick stainless steel)       | FTM 9 | N      | 10,1  | ≥ 7,8     |
| Shear (1kg, in <sup>2</sup> /glass)      | FTM 8 | min    | 28    | ≥ 18      |
| Minimum labelling temperature            |       | °C     | -20   |           |
| Minimum service temperature              |       | °C     | -40   |           |
| Maximum service temperature.             |       | °C     | +60   |           |

Liner

## Glassine White 80

*Description* Super-calendared translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* White

*Applications* For those applications where extra thickness of the backing paper is required such as wine labelling and filmic applications.

| Property  | Norm    | Units            | Value | Tolerance |
|-----------|---------|------------------|-------|-----------|
| Substance | ISO 536 | g/m <sup>2</sup> | 80    | 77-83     |
| Thickness | ISO 534 | µm               | 68    | 64-72     |

- Values are subject to change without notice. Last updated 1/1/2024.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

# TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.*