

Offset / A251 / WK130

Facestock

Offset

Description Calendered uncoated woodfree paper.

Applications Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)

Printing techniques Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, laser, hot stamping.

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|------------------|---------|-----------|
| Substance | 75 | g/m ² | 75 | 70-76 |
| Thickness | ISO 534 | µm | 70 | ± 2 |
| Bekk smoothness | ISO 5627 | s | ≥ 250 | |
| Brightness ISO | ISO 2470-2 | % | 101.5 | ± 2 |
| Whiteness CIE | ISO 11475 | % | 158.2 | ± 5 |
| Opacity | ISO 2471 | % | 89 | -2 |
| Tensile strength MD/CD | ISO 1924-2 | kN/m | 5.0/3.0 | -1 |

Adhesive

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 15,4 | ≥ 7,8 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 10,3 | ≥ 7,8 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 100 | ≥ 60 |
| Minimum labelling temperature | | °C | +5 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +80 | |

Liner

Kraft White 130

Description One-side coated white liner with high stiffness and stability. Available in split and solid back.

Color White

Applications Specially indicated for filmic applications.

| Property | Norm | Units | Value | Tolerance |
|------------------------|------------|------------------|-------------|---------------|
| Substance | ISO 536 | g/m ² | 130 | 124,8 - 135,2 |
| Thickness | ISO 534 | µm | 134 | 124 - 144 |
| Tensile strength MD/CD | ISO 1924-2 | kN/m | ≥6,7 / ≥4,3 | |

* Values are subject to change without notice. Last updated 1/1/2024.

* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.*