

Colour Matt Green / Supertack / YA62

Facestock

Colour Matt Green

Description Coated woodfree paper with a green matt colour finish.

Color Green

Applications POS promotional and advertising labels and office information labelling (address labels, file labels, etc.)

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), hot stamping, laser, conventional offset, offset UV, screen printing, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	76-86
Thickness	ISO 534	µm	82	75-90
Bekk smoothness	ISO 5627	s	≥ 180	
Tensile strength MD/CD	ISO 1924	kN/m	≥ 3,8/ ≥ 1,8	

Adhesive

Supertack

Description Specially strong and aggressive acrylic permanent adhesive with excellent tack and final adhesion. For difficult surfaces such as wood boxes, slightly wet surfaces, rough plastics and LDPE.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	14	≥ 11,5
Adhesion (Peel 180° 24h/kraft)	FTM 1	N/25mm	7,6	≥ 6,6
Adhesion (Peel 180° 24h/LDPE)	FTM 1	N/25mm	250	≥ 5,4
Shear (1kg, in ² /glass)	FTM 8	min	15	≥ 10
Tack (Quick Stick stainless steel)	FTM 9	N	12,3	≥ 9,8
Minimum labelling temperature		°C	-7	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+60	

Liner

Glassine Ambar 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	62	59-65
Thickness	ISO 534	µ	52	50-58

Certificates

Product approvals and usage certificates

Facestock

Colour Matt Green

Packaging and packaging waste Directive 94/62/CE

Electric and electronic equipment (RoHS)

Adhesive

Supertack

EN 71-3 Toy safety

Packaging and packaging waste Directive 94/62/CE

German Recommendation BfR XIV (ISEGA) - Adhesives

Liner

Glassine Ambar 62

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 3/24/2016.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC™ and FSC® chain of custody certificates upon request.