

Fluo Green / Supertack / GA62

Facestock

Fluo Green

Description Matt coated woodfree paper with a green fluorescent coating.

Color Green

Applications Eye-catching labels for pricing, display, promotions and warning signs.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), offset UV, conventional offset, screen printing, hot stamping, thermal transfer, laser.

| Property | Norm | Units | Value | Tolerance |
|------------------------|--------------|------------------|---------|--------------|
| Substance | ISO 536 | g/m ² | 80 | 76-84 |
| Thickness | ISO 534 | µm | 82 | 77-87 |
| Bekk smoothness | ISO 5627 | s | 250 | ≥ 200 |
| Tensile strength MD/CD | ISO 1924 | kN/m | 5.5/2.6 | ≥ 4.5/ ≥ 2.2 |
| Flatness | TAPPI UM 427 | mm | ≤30 | |

Adhesive

Supertack

Description Specially strong and aggressive acrylic permanent adhesive with excellent tack and final adhesion. For difficult surfaces such as wood boxes, slightly wet surfaces, rough plastics and LDPE.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 14 | ≥ 11,5 |
| Adhesion (Peel 180° 24h/kraft) | FTM 1 | N/25mm | 7,6 | ≥ 6,6 |
| Adhesion (Peel 180° 24h/LDPE) | FTM 1 | N/25mm | 250 | ≥ 5,4 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 12,3 | ≥ 9,8 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 15 | ≥ 10 |
| Minimum labelling temperature | | °C | -7 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +60 | |

Liner

Glassine Ambar 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

| Property | Norm | Units | Value | Tolerance |
|-----------|---------|------------------|-------|-----------|
| Substance | ISO 536 | g/m ² | 56 | 55-57 |
| Thickness | ISO 534 | µ | 48 | 46 - 49 |

- Values are subject to change without notice. Last updated 1/1/2024.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.*