Gloss 125 / SP123 / WK80

Facestock

Gloss 125

Description High substance gloss coated woodfre paper.

Applications For automatic labelling of meal trays thanks to its extra substance.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, hot stamping, thermal transfer, laser.

Norm	Units	Value	Tolerance
ISO 536	g/m²	125	± 4%
ISO 534	μm	91	± 4%
ISO 5627	S	1100	± 40%
ISO 2470-2	%	95.2	± 2
ISO 11475	%	119	± 3
ISO 8254-1	%	72	± 5
ISO 2471	%	93.5	-2
	ISO 536 ISO 534 ISO 5627 ISO 2470-2 ISO 11475 ISO 8254-1	ISO 536 g/m² ISO 534 μm ISO 5627 s ISO 2470-2 % ISO 11475 % ISO 8254-1 %	ISO 536 g/m² 125 ISO 534 μm 91 ISO 5627 s 1100 ISO 2470-2 % 95.2 ISO 11475 % 119 ISO 8254-1 % 72

Adhesive

SP123

Description Acrylic super-permanent adhesive with high tack. For difficult surfaces such as wood, some cardboards and plastics such as HDPE, PP, PET and PVC.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180º 20'/stainless steel)	FTM 1	N/25mm	17,2	≥ 13,5
Tack (Quick Stick stainless steel)	FTM 9	Ν	11	≥ 9,8
Shear (1kg, in²/glass)	FTM 8	min	100	≥ 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Kraft White 80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	± 4%
Thickness	ISO 534	μm	81	± 4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6/2,3	-0,6/-0,3

· Values are subject to change without notice. Last updated 1/1/2024.

* The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

Lecta Main Operational Offices Self-Adhesive Division Llull, 331 - 08019 Barcelona - Spain www.adestor.com