

Foil Silver / A251 / WK80

Facestock

Foil Bright Silver

Description Aluminium foil laminated on satin 50 gsm paper. Available in gloss finish.

Color Silver

Finish Gloss

Applications Decorative labels. High quality labels for cosmetics, spirits and the food industry in general.

Printing techniques Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), flexo solvent-base, UV flexo, screen printing, hot stamping, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	72	67.7 - 76.3
Thickness	ISO 534	µm	65	58.5 - 71.5

Adhesive

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

Shelf life From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	15,4	≥ 7,8
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Shear (1kg, in ² /glass)	FTM 8	min	100	≥ 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

Kraft White 80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	± 4%
Thickness	ISO 534	µm	81	± 4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6/2,3	-0,6/-0,3

- Values are subject to change without notice. Last updated 01/01/2024.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.