

# Matt Inkjet FSC® Certified / A251 / WG62

Facestock

## Matt Inkjet FSC® Certified

*Description* Matt coated woodfree paper for Inkjet printing. This product is sold as FSC® Mix Credit - FSC® C011032.

*Color* White

*Finish* Matt

*Applications* For all type of labels with excellent resolution. Used in the food and beverage industry, cosmetic products, retail or logistics.

*Printing techniques* Suitable for printing on inkjets.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	83	± 4
Thickness	ISO 534	µm	110	± 5
Whiteness CIE	ISO 11475	%	153	± 3
Opacity	ISO 2471	%	94	± 1

Adhesive

## A251

*Description* General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

*Shelf life* From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	15,4	≥ 7,8
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	100	≥ 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

## Glassine White 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	62	59 - 65
Thickness	ISO 534	µm	52	51 - 59

- Values are subject to change without notice. Last updated 1/1/2024.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO

45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

# TECHNICAL SPECIFICATIONS