

# Vellum / RA678 / GA 62

Facestock

## Vellum

*Description* Calendered uncoated woodfree paper.

*Color* White

*Finish* Matt

*Applications* Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)

*Printing techniques* Suitable for printing on flexo (all types), conventional offset, offset UV, Dry toner, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	75	± 5
Thickness	ISO 534	µm	70	± 2
Whiteness CIE	ISO 11475	%	158.2	± 5
Opacity	ISO 2471	%	89	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

Adhesive

## RA678

*Description* Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces

*Shelf life* From the date of manufacture 1 year in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel stainless steel 1 week)	FTM 1	N/25mm	1,7	1 - 2,9
Tack (Quick Stick stainless steel)	FTM 9	N	1,2	0,7 - 1,7
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	120	≥ 60
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

## Glassine Ambar 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	59	57 - 61
Thickness	ISO 534	µ	52	49 - 55

- Values are subject to change without notice. Last updated 1/1/2023.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

# TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC®** C011032 chain of custody certificates upon request.*