

# Foil Gold / A251 / GA62

Facestock

## Foil Bright Gold

*Description* Aluminium foil laminated on satin 50 gsm paper. Available in gloss and matt finish.

*Color* Gold

*Finish* Gloss, Matt

*Applications* Decorative labels. High quality labels for cosmetics, spirits and the food industry in general.

*Printing techniques* Suitable for printing on conventional offset, offset UV, letterpress (conventional and UV), UV flexo, flexo solvent-base, hot stamping, screen printing, thermal transfer.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	G/m <sup>2</sup>	72	67,7 - 76,3
Thickness	ISO 534	µm	65	58,5 - 71,5

Adhesive

## A251

*Description* General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.

*Shelf life* From the date of manufacture 2 years in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	15,4	≥ 7,8
Tack (Quick Stick stainless steel)	FTM 9	N	10,3	≥ 7,8
Shear (1kg, in <sup>2</sup> /glass)	FTM 8	min	100	≥ 60
Minimum labelling temperature		°C	+5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Liner

## Glassine Ambar 62

*Description* Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

*Color* Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m <sup>2</sup>	56	55-57
Thickness	ISO 534	µ	48	46 - 49

• Values are subject to change without notice. Last updated 1/1/2024.

• The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.