

Art 80

Facestock

Art 80

Description Superior gloss coated woodfree paper with high tensile strength.

Applications Top quality labels for multicolour printing. Extensively used in food and beverage industry, logistics, stationery and cosmetics products

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), screen printing, hot stamping, thermal transfer, laser, conventional offset, offset UV.

| Property | Norm | Units | Value | Tolerance |
|---------------------|------------|------------------|--------|-----------|
| Substance | ISO 536 | g/m ² | 80 | ± 4% |
| Thickness | ISO 534 | µm | 61 | ± 6 |
| Bekk smoothness | ISO 5627 | s | ≥ 1300 | |
| Brightness ISO | ISO 2470-2 | % | 117 | ± 3 |
| Paper gloss 20° | ISO 8254-1 | % | 72 | ± 5 |
| Opacity | ISO 2471 | % | 87 | -2 |
| Tensile strength MD | ISO 1924-2 | kN/m | 4,4 | -0,7 |

Certificates

Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

EN 1230 Sensorial analysis

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS)

Values are subject to change without notice. Last updated 01/01/2022.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.