

# Vellum Duplex

Facestock

## Vellum Duplex

*Description* Complex formed by Offset facestock (calendered uncoated woodfree paper), A251 permanent adhesive and yellow glassine liner 62 gsm.

*Applications* Extensively used in logistics for shipping and courier applications.

*Printing techniques* Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, hot stamping, laser.

| Property                   | Norm       | Units            | Value   | Tolerance |
|----------------------------|------------|------------------|---------|-----------|
| Substance                  | ISO 536    | g/m <sup>2</sup> | 135     | 70-76     |
| Thickness                  | ISO 534    | µm               | 137     | ± 2       |
| Bekk smoothness            | ISO 5627   | s                | ≥250    |           |
| Brightness ISO             | ISO 2470-2 | %                | 101.5   | ± 2       |
| Whiteness CIE              | ISO 11475  | %                | 158.2   | ± 5       |
| Opacity                    | ISO 2471   | %                | 89      | -2        |
| Wet tensile strength MD/CD | ISO 1924-2 | kN/m             | 5.0/3.0 | -1        |

- Values are subject to change without notice. Last updated 01/01/2023.

- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.