

CE432

Adhesive

CE432

Description A low tack acrylic semipermanent adhesive that permits repositioning upon application.

Shelf life From the date of manufacture 2 years in +20°C and RH 50%.

| Property | Norm | Units | Value | Tolerance |
|--|-------|--------|-------|-----------|
| Adhesion (Peel 180° 20'/stainless steel) | FTM 1 | N/25mm | 16,7 | ≥ 12,3 |
| Tack (Quick Stick stainless steel) | FTM 9 | N | 8,3 | ≥ 7,4 |
| Shear (1kg, in ² /glass) | FTM 8 | min | 55 | ≥ 30 |
| Minimum labelling temperature | | °C | +5 | |
| Minimum service temperature | | °C | -20 | |
| Maximum service temperature. | | °C | +80 | |

Certificates

Product approvals and usage certificates

German Recommendation BfR XIV (ISEGA) - Adhesives

- Values are subject to change without notice. Last updated 01/01/2022.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.