Colour Matt Blue / A251 / GA62

Facestock

Colour Matt Blue

Description Coated woodfree paper with a blue matt colour finish.

Color Blue

Applications POS promotional and advertising labels and office information labelling (address labels, file labels,

etc.)

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), hot stamping,

conventional offset, offset UV, screen printing, thermal transfer, laser.

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	80	76-86
Thickness	ISO 534	μm	82	75-90
Bekk smoothness	ISO 5627	s	≥ 180	
Tensile strength MD/CD	ISO 1924	kN/m	≥ 3,8/ ≥ 1,8	

Adhesive

A251

Description General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces. Shelf life From the date of manufacture 2 years in 20°C and RH 50%.

Norm	Units	Value	Tolerance
FTM 1	N/25mm	15,4	≥ 7,8
FTM 9	N	10,3	≥ 7,8
FTM 8	min	100	≥ 60
	°C	+5	
	°C	-20	
	°C	+80	
	FTM 1 FTM 9	FTM 1 N/25mm FTM 9 N FTM 8 min °C °C	FTM 1 N/25mm 15,4 FTM 9 N 10,3 FTM 8 min 100 °C +5 °C -20

Liner

Glassine Ambar 62

Super-calendered translucent glassine paper especially designed for automatic labelling Description applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color Yellow

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m²	56	55-57
Thickness	ISO 534	μ	48	46 - 49

Values are subject to change without notice. Last updated 01/01/2025.

Our self-adhesive mill is certified to the strictest environmental standards ISO 14001 and EMAS and has successfully completed audits for ISO 50001, ISO 9001 and ISO 45001 certification. Adestor paper products are available with PEFC and FSC® C011032 chain of custody certificates upon request.

The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.