

High Gloss WS 80 / HM100 / WG62

Facestock

High Gloss WS 80

Description Cast coated wet-strength woodfree paper with a high resistance to creasing, friction, breakage and tearing.

Applications Luxury labels requiring a wet-strength face stock. Specially indicated for beverage labels as wines, spirits, champagnes.

Printing techniques Suitable for printing on flexo (all types), letterpress (conventional and UV), conventional offset, offset UV, screen printing, stamping (hot and cold).

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	± 4%
Thickness	ISO 534	µm	76	± 4
Bekk smoothness	ISO 5627	s	1500	≥ 400
Brightness ISO	ISO 2470	%	89	± 2
Whiteness CIE	ISO 11475	%	106	± 5
Paper gloss	TAPPI T653 pm-07	%	40	± 5
Opacity	ISO 2471	%	90	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	3,9 / 2,6	-0,6 / -0,3
Wet tensile strength MD/CD	ISO 3781	kN/m	0,9 / 0,8	≥ 0,6 / ≥ 0,4

Adhesive

HM100

Description General use hot-melt adhesive for slightly wet conditions and difficult substrates.

Shelf life From the date of manufacture 1 year in 20°C and RH 50%.

Property	Norm	Units	Value	Tolerance
Adhesion (Peel 180° 20'/stainless steel)	FTM 1	N/25mm	18,4	≥ 14,7
Tack (Quick Stick stainless steel)	FTM 9	N	13,5	≥11
Shear (1kg, in ² /glass)	FTM 8	min	750	≥500
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+60	

Liner

Glassine White 62

Description Super-calendered translucent glassine paper especially designed for automatic labelling applications and photocell dispensing systems. This liner provides good tear resistance and smooth and regular thickness.

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	62	59 - 65
Thickness	ISO 534	µm	52	51 - 59

- Values are subject to change without notice. Last updated 01/01/2024.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

TECHNICAL SPECIFICATIONS

*Our self-adhesive mill is certified to the strictest environmental standards **ISO 14001 and EMAS** and has successfully completed audits for **ISO 50001, ISO 9001 and ISO 45001** certification. Adestor paper products are available with **PEFC and FSC® C011032** chain of custody certificates upon request.*